NEVNAILER INTERVIEW FEBRUARY - APRIL 2025 REDEMPTION PROMOTION



MAKE. MOVE. GO



UNLEASH **SUPERIOR** NAILING









BRUSHLESS CC FIR SPRING



NEW 18V Gasless 90mm Framing Nailer Kit

HIKOKI

- Aggressive nose for effortless skew nailing
- More Power sinks 90mm nails with ease
- Unique Air Spring Drive System
- Improved durable alloy magazine
- for quick loading and cleaning Configurable belt/rafter hook

Supplied with 2x 1080W Multi Volt battery, Fan-cooled Charger, Belt/Rafter Hook, Case 4.

Specifications

opeenieutiene		
Voltage		18V
Driving System		Air Spring Drive
Nail Type		Clipped Head
Nail Length		50 to 90mm
Nail Angle		30 to 34°
Depth Adjustment	Tool-less	\checkmark
Dry-fire lockout mechanism		\checkmark
Battery level indicator	On battery	\checkmark
LED light		\checkmark
Hook	Belt/Rafter	\checkmark
Magazine Capacity		50 Nails
Dimensions (H x D x L)		359 × 133 × 310m

MORE POWER

LIGHT WEIGHT

NR1890DCA 90MM FRAMING NAILER FEATURES



AGGRESSIVE NEW NOSE For effortless skew nailing even on extreme angles.

DURABLE ALLOY MAGAZINE

nail loading and easy cleaning.



NEW BELT / RAFTER HOOK Easily switch the hook to the left or right side.



POWERFUL LED LIGHT New lightweight magazine for quick Bright LED light for low light applications.



LIGHTWEIGHT SLIM BODY

FAST

NAILING

This new 18V Gasless Framing Nailer is lighter, slimmer and more ergonomic than before. Featuring an advanced new brushless motor and slimline high pressure air chamber, this lightweight, compact framing nailer delivers you more power and performance.

NEW 18V Gasless 90mm Framing Nailer Kit

NR1890DCA(GYZ)

- Improved design that's slimmer and lighter
- Aggressive nose for effortless skew nailing
- More Power sinks 90mm nails with ease
- Unique Air Spring Drive System
- Improved durable alloy magazine for quick loading and cleaning
- Configurable belt/rafter hook

Supplied with 1x 1080W Multi Volt battery, Fan-cooled Charger, Belt/Rafter Hook, Case 4

Specifications

Voltage		18V
Driving System		Air Spring Drive
Nail Type		Clipped Head
Nail Length		50 to 90mm
Nail Angle		30 to 34°
Depth Adjustment	Tool-less	\checkmark
Dry-fire lockout mechanism		\checkmark
Battery level indicator	On battery	\checkmark
LED light		\checkmark
Hook	Belt/Rafter	\checkmark
Magazine Capacity		50 Nails
Dimensions (H x D x L)		359 × 133 × 310mm



Scan for full tool specs







Scan for full tool specs



NEW 18V Gasless 90mm Framing Nailer Bare Tool

NR1890DCA(G4Z)

- Improved design that's slimmer and lighter
- Aggressive nose for effortless skew nailing
- More Power sinks 90mm nails with ease
- Unique Air Spring Drive System
- Improved durable alloy magazine for quick loading and cleaning
- Configurable belt/rafter hook

Supplied with Belt/Rafter Hook, Case 4. Supplied without battery and charger.



Specifications

-less
battery
/Rafte

Air Spring Drive Clipped Head 50 to 90mm 30 to 34° 50 Nails

18V



359 × 133 × 310mm Scan for full tool spece



NEW 18V Gasless Round Head Nailer Bare Tool NR1890DRA(W9Z)

- Improved design that's slimmer and lighter Aggressive nose for effortless skew nailing
- More Power sinks 90mm nails with ease
- Unique Air Spring Drive System
- Improved durable alloy magazine
- Supplied with Belt/Rafter Hook, Case 4. Supplied without battery and charger.

Specifications

opecifications				
Voltage		18V		
Driving System		Air Spring	g Drive	
Nail Type		Round H	ead	THE REPORT
Nail Length		50 to 90r	nm	一、台湾通道
Nail Angle		21°		
Depth Adjustment	Tool-less	\checkmark		
Dry-fire lockout mechanism		\checkmark		
Hook	Belt/Rafter	\checkmark		
Magazine Capacity		43 Nails		Scan for full tool

NEW 36V Gasless Duplex Formwork Nailer Bare Tool

NR3675DD(W6Z)

- Innovative duplex nailer for temporary fixings
- More Power Drives 75mm duplex nails with ease
- Unique Air Spring Drive System
- Dry-fire lockout system
- Supplied with Belt Hook, Case 4.
- Supplied without battery and charger.

Specifications

Voltage		36V	
Driving System		Air Spring Drive	
Nail Type		Duplex Nails	网络灰尾属
Nail Length		45 to 75mm	
Nail Angle		21°	
Depth Adjustment	Tool-less	\checkmark	and the second
Dry-fire lockout mechanism		\checkmark	同次 没告诉
Belt Hook	Steel	\checkmark	LET LA LET AND A DATA
Magazine Capacity		35 Nails	Scan for full tool specs.

18V Gasless 16G Angle Brad Nailer Bare Tool

NT1865DA(G4Z)

- Slim lightweight design
- More Power Sinks 65mm 16G C series nails with ease
- Unique Air Spring Drive System
- Dry-fire lockout system

Supplied with Belt Hook, No Mar Tip, Supplied without battery and charger.

Specifications

	Voltage		18V
	Driving System		Air Spring Drive
	Nail Type		16G C Series
	Nail Length		32 to 65mm
	Nail Angle		20°
	Depth Adjustment	Tool-less	\checkmark
	Dry-fire lockout mechanism		\checkmark
	Belt Hook	Steel	\checkmark
	Magazine Capacity		100 Nails

NEW 18V Gasless 45mm Coil Roof Nailer Bare Tool

NV1845DA(W6Z)

- Industry first Air Spring Drive coil roofing nailer
- More power drive 45mm wire coil nails with ease
- Fast nailing speeds fires more nails per second
- Unique Air Spring Drive System
- Accurate tool-less depth adjustment
- Supplied with Belt Hook, Case 4. Supplied without battery and charger.

Specifications

Voltage		18V	
Driving System		Air Spring Drive	
Nail Type		Wire Coil Nails	IN YEAR
Nail Length		25 to 45mm	一思愿
Nail Angle		16°	
Depth Adjustment	Tool-less	\checkmark	1.00
Dry-fire lockout mechanism		\checkmark	- 16 Ko
LED light		\checkmark	- 1990 1990
Magazine Capacity		120 Nails	Scan for ful

36V Gasless 65mm Metal Connector Nailer Kit

NR3665DA(GMZ)

- More power Drives 65mm product nails with ease
- Unique Air Spring Drive System
- Easily set the tip of the nailer at the hole of the metal connector for accurate nailing
- Designed for pre-punched hole metal connectors
- Supplied with 2x 1080W Multi Volt batteries, Rapid Charger, Belt Hook and Case

Specifications

Voltage		36V	
Driving System		Air Spring Drive	
Nail Type		Metal Connector	
Nail Length		38 to 65mm	交援開始回
Nail Angle		36°	56 200 M 200 C
Nose Type		Positive Probe	
Dry-fire lockout mechanism		\checkmark	一合変感動
Belt Hook	Steel	\checkmark	ETV/04/04/41/304
Magazine Capacity		31 Nails	Scan for full tool specs.

18V Gasless 18G Straight Brad Nailer Bare Tool

NT1850DA(G4Z)

- Improved new design that's slimmer and lighter
- Unique Air Spring Drive System
- More power Sinks 18G C1 series nails with ease
- New slimline nose for precision nailing
- Supplied with Belt Hook, 3x No-Mar Tip. Supplied without battery and charger.

Specifications

Scan for full tool specs.

Voltage		18V
Driving System		Air Spring Drive
Nail Type		18G C1 Series
Nail Length		16 to 50mm
Nail Angle		Straight
Depth Adjustment	Tool-less	\checkmark
Dry-fire lockout mechanism		\checkmark
Belt Hook	Steel	\checkmark
Magazine Capacity		100 Nails



HIKOKI

Scan for full tool specs.

HIKOKI

NEW 18V Gasless 15G Angle Finishing Nailer Bare Tool **NEW 18V** Gasless 16G Straight Brad Nailer Bare Tool

NT1865DAA(H4Z)

- Improved new design that's slimmer and lighter
- More power sinks 65mm 15G DA nails with ease
- Unique Air Spring Drive System
- New slimline nose for precision nailing
- Supplied with Belt Hook, 3x No Mar Tip.
- Supplied without battery and charger.

Specifications

Voltage		18V
Driving System		Air Spring Drive
Nail Type		15G DA Series
Nail Length		32 to 65mm
Nail Angle		34°
Depth Adjustment	Tool-less	\checkmark
Dry-fire lockout mechanism		\checkmark
Belt Hook	Steel	\checkmark
Magazine Capacity		100 Nails



Scan for full tool specs.

NEW 18V Cordless 23G Pin Nailer Bare Tool

NP18DSAL(W4Z)

- Compact and lightweight design
- Powerful nailing sinks 23G pins with ease
- Fast pin nailing speeds
- HiKOKI Spring Drive System
- Supplied with Belt Hook, Safety Glasses. Supplied without battery and charger.

Specifications

Voltage 18V Spring Drive Driving System Nail Type 23G Pin Nails Nail Length 16 to 35mm Nose Type Precision Nose Depth Adjustment Tool-less Dry-fire lockout mechanism Belt Hook Steel 100 Pins Magazine Capacity



NEW 18V Cordless 13mm Fine Wire Stapler Bare Tool

N1812DA(W4Z)

- Optimal use for fastening of fabrics,
- leather, foils, plastic and cardboard Fast stapling speed for fastest working progress
- Compact and lightweight design
- Slim design allows to set staples as close as 4mm
- Supplied with Belt Hook. Supplied without battery and charger.


Specifications

	opecifications		
	Voltage		18V
	Driving System		Spring Drive
	Staple Type	Crown width	13mm
	Staple Length		6 - 13mm
	Wire Thickness		0.5 x 0.7mm
	Quick stapling Speed		Up to 5 staples/sec
	Dry-fire lockout mechanism		\checkmark
	Belt Hook	Steel	\checkmark
	Magazine Capacity		150 Staples





s





NT1865DSA(H4Z)

- Improved new design that's slimmer and lighter
- More power sinks 65mm 16G C series nails with ease
- Unique Air Spring Drive System
- New slimline nose for precision nailing
- Supplied with Belt Hook, 3x No Mar Tip.
- Supplied without battery and charger.

Specifications







Scan for full tool specs.

NEW 18V Gasless 18G Stapler Bare Tool

N1804DA(W4Z)

- Compact and lightweight design for optimal operation
- Unique Air Spring Drive System
- Fast stapling drives 18G staples with ease
- Shoots up to 1000 staples with a BSL1820M
- Supplied with Belt Hook, Safety Glasses.
- Supplied without battery and charger.

Specifications



Voltage		18V	
Driving System		Air Spring Drive	
Staple Type	Crown Gauge	18G 1/4"	
Staple Length		13 to 38mm	765 6 776
Wire Thickness		1.25mm	61 - 270 - 172 - 274 - 185 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979 - 1979
Depth Adjustment	Tool-less	\checkmark	
LED Light		\checkmark	同語の思想
Belt Hook	Steel	\checkmark	
Magazine Capacity		100 Staples	Scan for full tool specs.

18V

Straight

100 Nails

 \checkmark

NEW 18V Cordless 10mm Fine Wire Stapler Bare Tool

N1810DA(W4Z)

- Optimal use for fastening of fabrics, leather, foils, plastics and cardboard
- Fast stapling speed for fastest working progress
- Compact and lightweight design
- Slim design allows to set staples as close as 4mm Supplied with Belt Hook.
- Supplied without battery and charger.

Specifications

aki		
HIK		
		Cere
	Carrow	-

Voltage		18V
Driving System		Spring Drive
Staple Type	Crown width	10mm
Staple Length		7 - 10mm
Wire Thickness		0.5 x 0.7mm
Quick stapling Speed		Up to 5 staples/sec
Dry-fire lockout mechanism		\checkmark
Belt Hook	Steel	\checkmark
Magazine Capacity		150 Staples



Scan for full tool specs

UNLEASH MORE POVER



21700 **HIGH OUTPUT** TABLESS CELLS



BSL3640MVT HIGH OUTPUT TABLESS BATTERY

NEW 36V Brushless Slide Compound Saw T-PWR Kit | NEW 36V Brushless Slide Compound Saw T-PWR Kit

The HiKOKI T-PWR Tabless Battery (BSL3640MVT) has been built

with less internal resistance allowing for more power to flow from

the tabless battery to the power tool increasing both the overload

ween HiKOKI's innovative T-PWR Tabless Cell vs. Conventional Cell.

capacity and tool speed. The diagram shows the difference bet-

The power of the conventional cell gets bottlenecked at a single

positive and negative tab while the tabless cell delivers free

fast-flowing power with almost no resistance.

LEARN

TABLESS CELL

TECHNOLOGY

C3612DRA(GTZ)

- New Torque Boost Technology
- XACT Cut for casting accurate cutting line
- 305mm blade diameter
- Supplied with 1x 2160W T-PWR Tabless Battery, 12A Max Fast Charger, TCT Blade, Wrench.

Specifications

specifications			
Voltage		36V	
Blade Diameter		305mm	
Mitre Angle	Left: 45°	Right: 57°	1012-47.7 (B)
Bevel Angle	Left: 45°	Right: 45°	
XACT Cut LED		\checkmark	
Torque Boost		\checkmark	
No Load Speed	HT: 3,200/min	AS: 4,000/min	
Motor Type		Brushless	LET D M MOOOD
Weight		26.2kg	Scan for full tool specs.

NEW 36V Brushless 254mm Table Saw T-PWR Kit

C3610DRJ(GTZ)

- Large table side (730 x 560mm)
- Accurate rack and pinion adjustment system
- Large adjustable rip fence
- Supplied with 1x 2160W T-PWR Tabless Battery, 12A Max Fast Charger, TCT Blade, Wrench.

Specifications			
Voltage		36V	
Blade Diameter		254mm	
Cutting Depth	90° 79mm	45° 57mm	
No Load Speed		5,000/min	and the second second
Rip Fence	L: 445mm	R: 889mm	CARL DIVERSITY OF THE
Table Size		730 x 560mm	
Motor Type		Brushless	
Adjustment System	Rack & Pinion	\checkmark	Scan for full tool specs.
Weight		29.5kg	Scan for full tool specs.





- Compact slide system
- Laser marker guide
- 255mm blade diameter

Supplied with 1x 2160W T-PWR Tabless Battery, 12A Max Fast Charger, TCT Blade, Wrench.

Voltage		36V	
Blade Diameter		255mm	Present Control of Con
Mitre Angle	Left: 55°	Right: 60°	In CALT IN
Bevel Angle	Left: 48°	Right: 48°	
Laser Marker		\checkmark	
LED Light		\checkmark	
No Load Speed		4,000/min	
Motor Type		Brushless	
Weight		20.6kg	Scan for full tool specs.

T-PWR 21700

TABLESS CELL

VS.

NEW 36V Brushless 185mm Circular Saw T-PWR Kit

C3607DB(GTZ)

- New Torque Boost Technology
- Smart AUTO switch function
- 185mm blade max cut 62mm at 90°

Supplied with 1x 2160W T-PWR Tabless Battery, 12A Max Fast Charger, TCT Blade, Wrench, Case.

Spec

Specifications		
Voltage		36V
Blade Diameter		185mm
Max Cut	90° - 62mm	45° - 47
Torque Boost		\checkmark
Modes	Auto Switch	High To
No Load Speed	6,000/min	4,500/r
Motor Type		Brushle
Hook Type	Rafter	\checkmark
Weight		4.6kg



HIKOKI TIPWR

CONVENTIONAL

21700 CELL

回遊城口

Scan for full tool specs

NEW 36V Brushless 165mm Plunge Saw T-PWR Kit



NEW 36V Brushless 125mm Angle Grinder T-PWR Kit

5.1kg

G3613DVE(GTZ)

Motor Type

Weight

Weiaht

Max Output Power

Weight

Powerful grinding with 1900W max output* Anti-kickback, restart, brake and overload protection Self protection mode and drop shut-off sensor Variable Speed and Automode Supplied with 1x 2160W T-PWR Tabless Battery, 12A Max Fast Charger, Wheel, Wrench, Case. Specifications Voltage 36V Wheel Diameter 125mm Spindle Thread M14 x 2 Hole Diameter 22.23mm No Load Speed Auto : 5,500/n 3,200 - 10,000/min Switch Type Slide Switch

Brushless

BSL3640MVT



HIKOK

Scan for full tool specs

NEW 18V Brushless 125mm Angle Grinder T-PWR Kit | NEW T-PWR Battery & 12A Max Fast Charger Kit

G1813DA(GTZ) Powerful grinding with 950W max output* Anti-kickback, restart and overload protection Slide Switch and Anti-vibration handle Soft-start safety feature HIKOKI Supplied with 1x 2160W T-PWR Tabless Battery, 12A Max Fast Charger, Wheel, Wrench, Case Specifications Voltage 18V Wheel Diameter 125mm Spindle Thread M14 x 2 Hole Diamete 22.23mm No Load Speed 8,000/min Switch Type Slide Switch Brushless Motor Type BSI 3640MVT 950W Max Output Power

1900W

2.8kg

Scan for full tool specs

UNLEASH FASTER CHARGING UC36YSL2 12A MAX FAST CHARGER

2.4kg

Unleash the new 12Amp max fast charger delivering lightening quick charging times with extra safety benefits. UC36YSL2 features the latest in cutting-edge cooling systems, 3-way protection including overcharging and overheating The UC36YSL2 is also features a highly visible charge status light easy to identify the charge status





45° - 47.5mm

High Torque

4.500/min

Brushless

NEW 36V Brushless 125mm Angle Grinder T-PWR Kit

G3613DVF(GTZ)

- Powerful grinding with 1900W max output*
- Anti-kickback, restart, brake and overload protection
- Self protection mode and deadman switch
- Variable Speed and Automode

Supplied with 1x 2160W T-PWR Tabless Battery, 12A Max Fast Charger, Wheel, Wrench, Case. 0-

Specifications

Voltage Wheel Diameter Spindle Thread Hole Diameter No Load Speed Switch Type Motor Type Max Output Power Weight

Auto : 5,500/min Paddle Switch Brushless BSI 3640MVT

125mm M14 x 2 22.23mm 3,200 - 10,000/min 1900W 2.8kg



HIKOK

Scan for full tool specs

HIKOK

NEW 18V Brushless 125mm Angle Grinder T-PWR Kit

36V

G1813DF(GTZ)

- Powerful grinding with 950W max output*
- Anti-kickback, restart, brake and
- overload protection
- Paddle Switch and Anti-vibration handle
- Variable Speed and Automode

Supplied with 1x 2160W T-PWR Tabless Battery, 12A Max Fast Charger, Wheel, Wrench, Case.

Specifications

Voltage		18V
Wheel Diameter		125mm
Spindle Thread		M14 x 2
Hole Diameter		22.23n
No Load Speed	Auto : 5,500/min	3,200 -
Switch Type	Paddle Switch	\checkmark
Motor Type	Brushless	\checkmark
Max Output Power	BSL3640MVT	950W
Weight		2.4kg

125mm M14 x 2 22.23mm 3,200 - 8,000/mir \checkmark 950W 2.4kg



Scan for full tool specs

HIKOK


UC36YSL2(HHZ)

- 2160W T-PWR Tabless Multi Volt Battery
- 1500 recharge cycles
- 12A max fast charger
- 40min charging time

Includes 1x BSL3640MVT, 1x UC36YSL2, Medium Multi Cruiser Case.

Specifications

BSL3640MVT Voltage Amp Hours 18V - 80Ah Max. Power Output BSL3640MVT Charging Time Cooling System 3-Way Protection USB A Output Status Charging Light Charging Voltage Li-ion Batteries 18V, 36V, Multi Volt





Scan for full tool specs





NEW TOOL INNOVATION

NEW 18V Gasless 90mm Framer & 16G Angle Brad Nailer Kit

KC18DCAM(GRZ)

- Improved design that's slimmer and lighter
- New aggressive new framer nose for effortless skew nailing
- HiKOKI's unquie Air Spring Drive System More power - Sinks nails with ease

Supplied with 2x 1080W Multi Volt batteries, Rapid Smart Charger, Belt Hook, 2x System Case 4s.

Specifications NF	R1890DCA	NT1865DA
Voltage	18V	18V
Driving System	Air Spring Drive	Air Spring Drive
Nail Type	Clipped Head	C Series
Nail Length	50 to 90mm	32 to 65mm
Nail Angle	30 to 34°	20°
Depth Adjustment	Tool-less	Tool-less
Dry-fire lockout mechanism	\checkmark	\checkmark
LED light	\checkmark	\checkmark
Hook	Belt / Rafter	Belt hook
Magazine Capacity	50 Nails	100 Nails
Dimensions (H x D x L)	359 x 133 x 310mm	323 x 105 x 298mm

NEW 18V Brushless 3-Tool Kit

KC18DE(GCZ)

18V Brushless 13mm Impact Drill DV18DE

18V Brushless 175Nm Impact Driver WH18DE

18V Brushless 165mm 'Deep Cut' Circular Saw C1806DB

Supplied with 2x 1080W Multi Volt Batteries, Fan-cooled Charger, 1x Case 3, 1x Case 4.

NEW 18V 160psi Dual Pump Inflator Bare Tool

UP18DA(W4Z)

- High pressure mode for tyre inflation
- High volume mode for air beds, inflatables etc
- Auto stop function
- Powers via battery or 12V DC adaptor Supplied with 12V DC adaptor

Supplied without batteries and charger

Specifications

Voltage		18V	
Filling Capacity	High: 16L/min	Low: 430L/min	
Max Pressure	11 Bar	160PSI	in the second second
Hose Length	HP: 1200mm	HV: 490mm	
LED Light		\checkmark	
Auto Stop Function		\checkmark	
Backlit Display		\checkmark	
Weight		3.8kg	CONTRACTOR -
Dimensions (H x D x L)		328 x 185 x 259mm	Scan for full tool specs

NEW 18V Brushless 125mm Circular Saw Bare Tool

C1805DA(W2Z)

- High powered and fast speed cutting
- Lightweight, compact and accurate cutting
- Fine adjustment system
- Silent mode, overload protection
- and blower function Supplied with Blade, Guide, Dust Adaptor, Wrench, Case 4.

Supplied without batteries and charger Specifications



NEW 18V HEPA 13 Wet & Dry Vac Bare Tool

RP18DA(W4Z)

- Compact, lightweight and portable
- Two suction modes (Eco / Boost Mode)
- Press clean button

HIKOKI

- HEPA 13 filter
- Supplied without batteries and charger. Includes hose, tubes, crevice & wide nozzle

Specifications

Voltage		18V	
Filter Type		HEPA 13	
Suction Work Rate	Boost: 80W	Eco: 35W	
Runtime (BSL36B18X)	Eco - 45min	Boost - 26min	
Max Airflow	Hose - 1.8m ³ /min	Motor - 2.1m ³ /min	
Max Vac Pressure	Hose - 11kPa	Motor - 12kPa	
Protection Class		IPX4	
Weight		5.1kg	ELEND SOME
Dimensions (H x D x L)		330 x 210 x 393mm	Scan for full tool specs

NEW 36V SDS-MAX Demolition Hammer Bare Tool

H3641DA(H2Z)

- Equivalent performance to H41MB2 AC model
- Compact and lightweight model
- Low Vibration Handle (LVH)
- Tool angle adjustment system

Supplied without batteries and charger Includes side handle, bullpoint attachment, case

Creation

Specifications		
Voltage		36V
Impact Rate	Lo - 1,500/min	Hi - 2,880/min
Full Load Vibration		9.7m/s ²
Impact Energy		6.8J
Low Vibration Handle		\checkmark
4-Step Impact Rate		\checkmark
Multiple Bit Angle	12 Angles	\checkmark
Dimensions (H x D x L)		463 x 95 x 248mm
Weight		5.8kg

BEST POWER TO WEIGHT RATIO



Impact Wrench Bare Tool

Specification	S	
Voltage		18V
Square Drive	1/2"	12.7mm
Max Torque		345Nm
Modes	4 Speed Modes	4 Impact Modes
No Load Speed		0 - 2,800/min
Impact Modes		0 - 4,000/min
Capacity Bolt	OB M10 - M20	HTB M10 - M16
IP Rated		IP56
Weight		2.0kg

- 4 Mode selector
- IP56 Water and Dust protection

- Huge 1900Nm tightening torque

ltage		18V
luare Drive	3/4"	19mm
ax Torque		1,900Nm
odes	4 Speed Modes	4 Impact M
b Load Speed		0 - 1,500/m
pact Modes		0 - 2,600/m
apacity Bolt	OB M10 - M26	HTB M10 -
Rated		IP56

tool specs.

Weight



Í	KY	
likoki	N	
8		

Scan for full tool specs.

Scan for full tool specs.




同逆

Scan for full tool specs

Hikoki	Ð		







		18V
Э	3/4"	19mm
		1,900Nm
	4 Speed Modes	4 Impact Modes
eed		0 - 1,500/min
es		0 - 2,600/min
lt	OB M10 - M26	HTB M10 - M27
		IP56



18V Cordless 450g Grease Gun Bare Tool

AL18DA(G4Z)

- Variable flow dial with 10 pre-set discharge pressure settings
- 3-way filling system
- Two mode operation (High/Low) Supplied without batteries and charge Includes Shoulder Strap, LED light

Specifications

	Voltage		18V
	Flow Rate	High: 297mm	Low: 115mL
	Max Pressure		69/41MPa
	Speed Modes		2 Modes
	Flow Settings		10 Flow Settings
	Hose Length		1200mm
	Cartridge Size	450g	\checkmark
	LED Light	2x LED Lights	\checkmark
	Weight		4.9kg

	 Variable flow dial with 10 pre-set discharge pressure settings 3-way filling system Two mode operation (High/Low) Supplied with 1 x BSL36A18X, Rapid Character 4, Shoulder Strap, LED light. 		
	Voltage		18V
	Flow Rate	High: 297mm	Low
al Médical International	Max Pressure		69/4
	Speed Modes		2 M
	Flow Settings		10 F
	Hose Length		1200
	Cartridge Size	450g	\checkmark
	LED Light	2v LED Lights	./

AL18DA(GRZ)

Scan for full tool specs.

, ,		
Two mode ope	ration (High/L	ow) 🖉
Supplied with 1 x B	SL36A18X, Rapi	d Charger,
Case 4, Shoulder S	trap, LED light.	
Specifications		
Voltage		18V
Flow Rate	High: 297mm	Low: 115mL
Max Pressure		69/41MPa
Speed Modes		2 Modes
Flow Settings		10 Flow Settings
Hose Length		1200mm
Cartridge Size	450g	\checkmark
LED Light	2x LED Lights	\checkmark
Weight		4.9kg



Scan for full tool spece

HIKOKI REDEMPTIONS





OPTION 1 3:133 **18V HEAT GUN WORTH \$289**

OPTION 2 18V 125MM ORBITAL SANDER **WORTH \$259**

REDEEM A BONUS 18V HEAT GUN OR ORBITAL SANDER OR WORKSITE BLOWER BARE TOOL WHEN YOU BUY A QUALIFYING 4+ TOOL COMBO KIT





Not in conjunction with any other bonus offer. While stocks last. Bonus is a choice of either a

RH18DA(G4Z), RB18DC(G4Z) or SV1813DA(G4Z). Bonus value is based on MSRP. Redemption items

will be dispatched within 6 weeks of receipt claim. Proof of purchase and photo of barcode required.

For terms & conditions, list of qualifying kits and to redeem, go to www.hikoki.co.nz/promotions/

TERMS & CONDITIONS APPLY. Offer valid for purchases from 1 February - 30 April 2025. Redemption closes on 15th May 2025.

TERMS & CONDITIONS APPLY.

Offer valid for purchases from 1 February - 30 April 2025. Redemption closes on 15th May 2025. Not in conjunction with any other bonus offer. While stocks last. Bonus is a G18DSL2(H5Z) 18V 125mm Angle Grinder. Bonus value is based on MSRP. Redemption items will be dispatched within 6 weeks of receipt claim. Proof of purchase and photo of barcode required. For terms & conditions, list of qualifying kits and to redeem, go to www.hikoki.co.nz/promotions/





\$339 VIA REDEMPTION WHEN YOU PURCHASE ANY **QUALIFYING DRILL & DRIVER COMBO KIT**



QUALIFYING KITS



KC36DC(GRZ)





OPTION 3 18V WORKSITE BLOWER WORTH \$175





KC18368DE(GRZ)





HIKOKI REDEMPTIONS

REDEEM A

5

Li-ion 18v

ΗίΚΟΚΙ

ΗίΚΟΚΙ

REDEEM A BONUS 18V LI-ION BATTERY

WORTH \$169 WHEN YOU BUY 2x QUALIFYING 18V BARE TOOLS

Terms & Conditions Apply. Offer valid for purchases from 1 February – 30 April 2025.

Redemption closes on 15th May 2025. Not in conjunction with any other bonus offer. Bonus is a BSL1820M. While stocks last. Purchases must be transacted on one receipt to qualify. Proof of purchase and photo of barcode required. Bonus value is based on MSRP. For terms & conditions, list of qualifying 18V Bare Tools and to redeem, go to www.hikoki.co.nz/promotions/

2.0



SCAN TO REDEEM